


// FAAE / FAAT – L-SHAPED EDGING PROFILES MADE OF ALUMINUM

| | |
|--|--|
| Item-no. | FAAE / FAAT - matt |
| Product group | Tile trim |
| Height FAAE | 2 / 3 / 4.5* / 6* ** / 8* ** / 9** / 10* ** / 11* ** / 12.5* ** / 15* ** / 16.5** / 18.5** / 20* / 22** / 25** mm |
| Height FAAT + FAAE-M/-BS | 8 / 10 / 12.5 mm |
| Length FAAE | 250 / 270 / 300 cm (*only available in 270 cm / **only available in 300 cm) |
| Length FAAT + FAAE-M/-BS | 250 cm |
| Surface FAAE | FAAE: silver anodized |
| Surface FAAT + FAAE-M/-BS | FAAT: titanium anodized FAAE-M: brass anodized FAAE-BS: bronze anodized brushed |
| Thickness | approx. 1.5 mm |
| Material | Aluminum 6060 in accordance to DIN EN 755-1 (extruded Aluminum) AlMgSi0.5 |
| Properties | Surface anodised in accordance to DIN 17611 |
| Fire resistance in accordance to DIN EN 13501 | A1 (non-flammable) |
| Linear coefficient of expansion | $24 \times 10^{-6} \text{ m/m}^\circ\text{C}$ |
| Density approx | 2.7 - 2.8 kg/dm ³ |
| Hardness approx | 70 - 80 HB |
| Chemical resistance | approx. 4.5 - 8.5 pH |
| Melting point at | approx. 660°C |
| Other Properties | Production in accordance to DIN EN 120-1 Aluminum and Aluminum alloys – Technical delivery terms. Factory production controls in accordance to DIN 18200. |
| Drawing |  |