

// FVAE / FVGC / FVHS / FVTH / FVTS – ROUND EDGE PROFILES CLOSED MADE OF ALUMINUM

Item-no.	FVAE / FVGC / FVHS / FVTH / FVTS - high-gloss
Product group	Tile trim
Height	6* / 8 / 10 / 12,5 mm (* only in silver high-gloss anodized)
Length	250 cm
Thickness	approx. 1.5 mm
Material	Aluminum 6060 in accordance to DIN EN 755-1 (extruded Aluminum) AlMgSi0,5
Surface	FVGC: silver high-gloss anodized FVHS: silver high-gloss anodized brushed FVTH: titanium high-gloss anodized FVTS: titanium high-gloss anodized brushed FVAE-SWG: black high-gloss anodized FVAE-SWS: black high-gloss anodized brushed FVAE-KGS: copper high-gloss anodized brushed
Properties	Surface anodised in accordance to DIN 17611
Fire resistance in accordance to DIN EN 13501	A1 (non-flammable)
Linear coefficient of expansion	$24 \times 10^{-6} \text{ m/m}^\circ\text{C}$
Density approx	2.7 - 2.8 kg/dm ³
Hardness approx	70 - 80 HB
Chemical resistance	approx. 4.5 - 8.5 pH
Melting point at	approx. 660°C
Other Properties	Production in accordance to DIN EN 120-1 Aluminum and Aluminum alloys – Technical delivery terms. Factory production controls in accordance to DIN 18200.
Drawing	