



fuma // SEAL - INTERNAL AND EXTERNAL CORNERS

with AbP test certificate

Item-no.	FDB 150-PP/I + FDB 150-PP/A	
Product group	Sealing	
Application	Sealing for construction corners in addition with water-proofing tapes.	
Leg length	FDB 150-PP/I: 120 mm FDB 150-PP/A: 150 mm	
Height	approx. 60/90 mm	
Material thickness	approx. 0.6 mm	
Material	Substrate: Two outer layers of polypropylene non-woven. Coating: Thermoplastic elastomere, resistant to ageing	
Color	grey	
Temperature resistance	-30°C - +90°C	
Burst pressure	approx. 1,5 bar	
Resistance to water pressure DIN EN 1928 (Version B)	approx. 1,5 bar	
Chemical resistance (after 7 days room temperature)	Lactic acid 5%	resistant
	Sulphuric acid 35%	resistant
	Hydrochloric acid 3%	resistant
	Citric acid 100 g/l	resistant
	Sodium hypochlorite 0,3 g/l	resistant
	Salt water (20 g/l Sea water salt)	resistant
Product picture	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>FDB 150-PP/I</p> </div> <div style="text-align: center;">  <p>FDB 150-PP/A</p> </div> </div>	