

**fuma // SEAL – PIPE COLLAR FOR WALL**

with AbP test certificate

<b>Item-no.</b>	FDB 150-PP/W	
<b>Product group</b>	Sealing	
<b>Dimension</b>	120 x 120 mm	
<b>Hole diameter</b>	15 mm	
<b>Material thickness</b>	approx. 1 mm	
<b>Material weight</b>	approx. 7 g / Piece	
<b>Material</b>	Substrate: Two outer layers of polypropylene non-woven Coating: Thermoplastic elastomere, resistant to ageing	
<b>Color</b>	grey	
<b>Temperature resistance</b>	-30°C – +90°C	
<b>Burst pressure</b>	approx. 1,5 bar	
<b>Resistance to water pressure DIN EN 1928 (Version B)</b>	approx. 1,5 bar	
<b>UV-Resistance</b>	min. 500 h	
<b>Chemical resistance (after 7 days room temperature)</b>	Lactic acid 5%	resistant
	Sulphuric acid 35%	resistant
	Hydrochloric acid 3%	resistant
	Citric acid 100 g/l	resistant
	Sodium hypochlorite 0,3 g/l	resistant
	Potassium hydroxide 3% / 20%	resistant
	Salt water (20 g/l Sea water salt)	resistant
<b>Product picture</b>		